

Technical Data - PU Sealer

20/11/2025



PRODUCT DESCRIPTION

PU Sealer is a low viscosity moisture curing polyurethane prepolymer based on toluene diisocyanate. When cured it produces a remarkably tough flexible film highly resistant to abrasion, chemical attack, oil, grease and water penetration. Its superb wearing properties make it ideal for flooring subject to heavy commercial use.

PURPOSE

For coating and sealing concrete floors and walls in factories, warehouses, garages etc. to protect the surface from chemical attack, oils and greases and to prevent wear and dusting. **PU Sealer** also resists staining by foodstuffs such as ketchup, red wine, vinegar, coffee, mustard & blackcurrant juice.

SPECIAL PROPERTIES

- Excellent chemical and abrasion resistance
- A thorough, flexible film at wide temperature range
- Applied by brush, roller or sprayer
- Single component
- Quick drying
- Excellent waterproofing qualities
- Totally Aliphatic (UV stable, will not yellow)

APPLICATION INSTRUCTIONS

Surfaces must be clean, dry, mature and free from contamination. Laitenance must be removed. Grit blasting, acid etching or grinding are all acceptable methods where preparation is required. Mechanical preparation may be required if the surface is very dense (e.g. powerfloated finish) or if any surface coating is present. The container contents should be well stirred. Priming is not normally required. The material can be used straight from container, applied by brush, roller or squeegee to obtain an even coating. Two coats are normally required on porous surfaces, or where maximum impermeability is required. Allow the first coat to dry for 2-3 hours before applying the second. The second coat must be applied within 24 hours to ensure good intercoat adhesion. If a slip resistant surface is required, anti-slip aggregate may be added into the second coat. Immediately after use, clean all tools with cleaning solvent.

APPROXIMATE COVERAGE

Up to 4 to 7m² per kg

STORAGE

Store in a cool, dry place. Shelf month is 12 months in original unopened containers.

PACKAGING

4 & 20kg metal drums.

SPECIFICATION CLAUSE

"The above film property guidelines are based on material cured under ideal conditions and no guarantees are implied or liabilities accepted. The end user should test thoroughly to ensure suitability for intended use."

HEALTH AND SAFETY

Ensure adequate ventilation. Breathing equipment will be required in confined spaces. For more detailed information refer to Safety Data Sheet and product labels.

TECHNICAL SERVICES

For further information, call our technical dept on:
UK (01635) 202224
International +44(0) 1635 202224

E-Mail: info@picsuk.com
Website: www.picsuk.com

WARRANTY

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

MANUFACTURED BY PICS

Unit 2 & 4, Red Shute Hill Ind. Est. Hermitage, Nr Newbury
Berkshire RG18 9QL

Tel: +44 (0) 1635 202224 E-Mail: info@picsuk.com Web: www.picsuk.com

