Technical Data - Acid Wash

15/04/2026

PICS
www.picsuk.com

PRODUCT DESCRIPTION

Acid Wash is a clear dilute acid.

PURPOSE

Acid Wash is used to ensure sufficient Antique Release Agent (RA) is removed from the surface of the imprinted concrete. This process is generally undertaken 4 days after the concrete has been imprinted and consists of sweeping off the bulk of the residual powder (and disposing of it accordingly), applying Release Agent Wash and finally applying an **Acid Wash** to ensure that sufficient RA is removed from the surface prior to sealing.

SPECIAL PROPERTIES

- Ready to use strength
- Enables removal of excess antiquing (RA)
- Correct use reduces tyre tear and future sealer issues

APPLICATION INSTRUCTIONS

Acid Wash is easy and safe to use, however **GREAT CARE** must be taken to undertake the process in a controlled and diligent manner. Incorrect or over enthusiastic use will potentially cause irreversible damage to the surface of the newly installed PIC.

It is essential that the surface of the paving is **FULLY SATURATED** with water prior to application of **Acid Wash** and that the product is applied sparingly and in a controlled manner with an all plastic sprayer. (Never use a bucket and brush approach). Once applied the **Acid Wash** should be very lightly moved around with a soft broom.

Leave for a few minutes to react with the concrete surface before thoroughly washing with a powerful water jet, in order to remove the weakened concrete surface and consequently the excess RA.

Acid Wash should not be overapplied and in most cases 2 or 3 small application and wash cycles are far better and safer than one generous application. Especially when not familiar with the process.

Any questions call the technical department and / or read the full application instructions available on request.

PACKAGING

5 & 25 litre plastic jerry can.

STORAGE

Store at minimum 5°C. Do not allow to freeze.

APPROXIMATE COVERAGE

3–4 m² per litre depending on application.

HEALTH AND SAFETY

Do not ingest. Wear gloves, protective glasses and clothing at all times. Avoid contact with eyes and skin. If in contact with eyes, wash immediately. Keep out of reach of children and animals. Refer to Safety Data Sheet for further information.

TECHNICAL SERVICES

For further information, call our technical dept on:

UK	(01635) 202224
International	+44(0) 1635 202224
E-Mail:	info@picsuk.com
Website:	www.picsuk.com

WARRANTY

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

MANUFACTURED BY PICS

Unit 2 & 4, Red Shute Hill Ind. Est. Hermitage, Nr Newbury
Berkshire RG18 9QL

Tel: +44 (0) 1635 202224 **E-Mail:** info@picsuk.com **Web:** www.picsuk.com