Technical Data - Primer Pro Slurry

05/06/2025

PICS
www.picsuk.com

PRODUCT DESCRIPTION

Primer Pro Slurry is a grey cement based polymer modified priming slurry. To seal, prime and bond natural stone, porcelain, paving slabs and other paving materials to the new bed, whilst installing new paved areas.

PURPOSE

Primer Pro Slurry should be used to seal and prime natural stone, porcelain paving slabs, and other paving materials to a fresh bed of mortar and can be used externally and internally. The product should be mixed at a ratio of 5:1 (**Primer Pro Slurry**: Water).

SPECIAL PROPERTIES

- Bonding Agent
- Seals porous materials
- External or internal use
- Reduces reflective staining on surface
- Creates strong bond between paving unit and mortar bed

APPLICATION INSTRUCTIONS

The underside of the slab must be suitable, fully clean and free from dirt. Place 5 litres of clean water into a mixing vessel e.g. bucket and open the 25kg **Primer Pro Slurry** bag and tip material into the mixing vessel. For the 15kg container version, place 1.5 litres of water into the mixing vessel for each 7.5kg bag of material. Mix the material using a plasterers mixing paddle or similar for 2 minutes until a smooth and creamy mix consistency is formed, if a more fluid consistency is required by the applicator then additional water can be used at the customer's discretion. Pot open life of the product is between 8 – 16 hours subject to ambient air temperature and the product being stored within a closed storage vessel. Apply the fresh mix to the underside of the slab with a suitable brush, taking great care not to contaminate the top surface. Place the primed slab onto the fresh mortar bed while the primer is still wet / tacky.

CLEANING OF SURFACES, AREAS AND TOOLS

Primer Pro Slurry has excellent adhesive properties and therefore is difficult to remove once set. Spills or splashes on any structure, including the top surface of the paving until should be washed immediately with clean water.

PACKAGING

25kg bags and 15kg containers (2 x 7.5kg).

COVERAGE

15-30m² per 25kg and 9-18m² per 15kg for priming subject to thickness of application. Porosity of the substrate being primed will affect the coverage. Products with high porosity will be closer to the lower coverage rate.

STORAGE

Store in a cool, dry place.

TECHNICAL DATA

When used within paving systems **Primer Pro Slurry** meets the recommended performance characteristics described within BS7533.

HEALTH AND SAFETY

Primer Pro Slurry can cause irritation, skin burns and is non-flammable. It is recommended safety glasses, gloves and appropriate clothing are worn and avoid contact with skin. Do not smoke. Keep area well ventilated. Refer to the Safety Data Sheet for further information.

TECHNICAL SERVICES

For further information, call our technical dept on:

UK	(01635) 202224
International	+44(0) 1635 202224
E-Mail:	info@picsuk.com
Website:	www.picsuk.com

WARRANTY

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

MANUFACTURED BY PICS

Unit 2 & 4, Red Shute Hill Ind. Est. Hermitage, Nr Newbury
Berkshire RG18 9QL

Tel: +44 (0) 1635 202224 **E-Mail:** info@picsuk.com **Web:** www.picsuk.com